

Surveillance HDD

Data Sheet

The New Generation SV Drive

- The industry's first surveillance-optimized hard drive precision-tuned for high write surveillance workloads operating 24x7
- Capacities up to 8TB support 64 cameras per drive and 8+¹ drives per system
- Engineered for workloads of 180TB/year, three times that of desktop drives
- Low power consumption and startup current to minimize heat and vibration emission, improving long-term drive reliability
- Tarnish-resistant components to help protect drive from environmental elements, increasing field reliability
- Customize power settings for incremental savings during system downtime without compromising time to record
- Reliable performance in multi-drive systems with support from RV sensors
- Optional 3-year +Rescue Data Recovery Service plan to help protect against data loss from viruses, software issues or mechanical and electrical breakdowns

Best-Fit Applications

- NVR
- Embedded SDVR
- Hybrid SDVR
- Surveillance DVR

¹ Drives with Rotational Vibration sensors can be used in systems with 8+ drive bays. Drives without Rotational Vibration are ideal for systems with 8 or fewer drives.





Surveillance HDD



Specifications	Surveillance HDD						
Capacity	8TB	6TB	5TB	4TB	3TB	2TB	1TB
Standard Model Numbers	ST8000VX0002	ST6000VX0001	ST5000VX0001	ST4000VX000	ST3000VX006	ST2000VX003	ST1000VX001
+Rescue Model Numbers	ST8000VX0012	ST6000VX0011	ST5000VX0011	ST4000VX002	ST3000VX005	ST2000VX005	ST1000VX003
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Cache	256MB	128MB	128MB	64MB	64MB	64MB	64MB
Bytes per Sector	4096	4096	4096	4096	4096	4096	4096
Performance							
R/V (Rotational Vibration) Sensor	Yes	Yes	Yes	Yes	No	No	No
Drive bays supported	8+	8+	8+	8+	1 to 8	1 to 8	1 to 8
Cameras Supported	Up to 64	Up to 64	Up to 64	Up to 64	Up to 64	Up to 64	Up to 64
Max Sustainable Transfer Rate	230MB/s	180MB/s	180MB/s	180MB/s	180MB/s	180MB/s	180MB/s
+Rescue Data Recovery Service							
3-Year Option With +Rescue Model	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Voltage							
Voltage Tolerance, Inc. Noise (5V)	±5%	±5%	±5%	±5%	±5%	±5%	±5%
Voltage Tolerance, Inc. Noise (12V)	±10%	±10%	±10%	±10%	±10%	±10%	±10%
Power Management							
Startup Power (12V, A)	1.8	1.8	1.8	1.8	1.8	1.8	1.8
Average Operating Power	9.0W	9.0W	9.0W	5.6W	5.6W	5.6W	5.6W
Idle Average	7.6W	7.2W	7.2W	4.0W	4.0W	4.0W	4.0W
Standby Mode	0.6W	0.6W	0.6W	0.5W	0.5W	0.5W	0.5W
Sleep Mode	0.6W	0.6W	0.6W	0.5W	0.5W	0.5W	0.5W
Environmental/Temperature							
Operating (ambient, min)	5°C	5°C	5°C	0°C	0°C	0°C	0°C
Operating (drive case, max)	60°C	60°C	60°C	70°C	70°C	70°C	70°C
Nonoperating (ambient, min)	-40°C	-40°C	-40°C	-40°C	-40°C	-40°C	-40°C
Nonoperating (ambient, max)	70°C	70°C	70°C	70°C	70°C	70°C	70°C
Reliability							
Tamish Resistant ¹	Yes	Yes	Yes	Yes	No	No	No
Load/Unload Cycles	300,000	300,000	300,000	300,000	300,000	300,000	300,000
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E15	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14	1 per 10E14
Mean Time Between Failures	1,000,000hr	1,000,000hr	1,000,000hr	1,000,000hr	1,000,000hr	1,000,000hr	1,000,000hr
Power-On Hours	8760	8760	8760	8760	8760	8760	8760
Warranty, Limited (years)	3	3	3	3	3	3	3
Physical							
Height	26.11mm	26.11mm	26.11mm	26.11mm	26.11mm	26.11mm	19.99mm
Height	1.028in	1.028in	1.028in	1.028in	1.028in	1.028in	0.787in
Width	101.85mm	101.85mm	101.85mm	101.6mm	101.6mm	101.6mm	101.60mm
Width	4.010in	4.010in	4.010in	4.0in	4.0in	4.0in	4.0in
Depth	147.00mm	147.00mm	147.00mm	146.99mm	146.99mm	146.99mm	146.99mm
Depth	5.878in	5.878in	5.878in	5.787in	5.787in	5.787in	5.787in
Typical Weight	780g	780g	780g	610g	610g	610g	400g
Typical Weight	1.72lb	1.72lb	1.72lb	1.345lb	1.345lb	1.345lb	0.88lb
Carton Unit Quantity	20	20	20	20	20	20	25
Cartons per Pallet	40	40	40	40	40	40	40
Cartons per Layer	8	8	8	8	8	8	8

Specifications	SV35 Series™		
	3TB	2TB	1TB
Capacity	3TB	2TB	1TB
Standard Model Numbers	ST3000VX000	ST2000VX000	ST1000VX000
+Rescue Model Numbers	ST3000VX004	ST2000VX004	ST1000VX002
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
Cache	64MB	64MB	64MB
Bytes per Sector	4096	4096	4096
Performance			
R/V (Rotational Vibration) Sensor	No	No	No
Drive bays supported	1 to 8	1 to 8	1 to 8
Cameras Supported	Up to 32	Up to 32	Up to 32
Max Sustainable Transfer Rate	210MB/s	210MB/s	210MB/s
+Rescue Data Recovery Service			
3-Year Option With +Rescue Model	Yes	Yes	Yes
Voltage			
Voltage Tolerance, Inc. Noise (5V)	±5%	±5%	±5%
Voltage Tolerance, Inc. Noise (12V)	+10%/–7.5%	+10%/–7.5%	+10%/–7.5%
Power Management			
Startup Power (12V, A)	2.0	2.0	2.0
Average Operating Power	8.0W	8.0W	5.90W
Idle Average	5.4W	5.4W	3.36W
Standby Mode	0.75W	0.75W	0.63W
Sleep Mode	0.75W	0.75W	0.63W
Environmental/Temperature			
Operating (ambient, min)	0°C	0°C	0°C
Operating (drive case, max)	70°C	70°C	70°C
Nonoperating (ambient, min)	–40°C	–40°C	–40°C
Nonoperating (ambient, max)	70°C	70°C	70°C
Reliability			
Tamish Resistant ¹	—	—	—
Load/Unload Cycles	300,000	300,000	300,000
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E14	1 per 10E14	1 per 10E14
Mean Time Between Failures	1,000,000hr	1,000,000hr	1,000,000hr
Power-On Hours	8760	8760	8760
Warranty, Limited (years)	3	3	3
Physical			
Height	26.11mm	26.11mm	19.99mm
Height	1.028in	1.028in	0.787in
Width	101.6mm	101.6mm	101.6mm
Width	4.0in	4.0in	4.0in
Depth	146.99mm	146.99mm	146.99mm
Depth	5.787in	5.787in	5.787in
Typical Weight	626g	626g	400g
Typical Weight	1.38lb	1.38lb	0.88lb
Carton Unit Quantity	20	20	25
Cartons per Pallet	40	40	40
Cartons per Layer	8	8	8

1 Product will ship with tarnish-resistant components in early 2016.

SEAGATE.COM

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000

ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888

EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2015 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. SV35 Series and +Rescue are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and may be controlled for export, import and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS1679.15-1509US September 2015